

# Carbolink's Solutions for Repairing Compounds

## CLI Crack Seal (AC 100)



**Repairing Compounds Product  
Specifications & Technical  
Data Sheets(TDS)**

India's Most Preferred  
Construction Chemical Manufacturing Brand



**Carbolink India Pvt. Ltd.**

[WWW.CARBOLINKINDIA.COM](http://WWW.CARBOLINKINDIA.COM)



# Carbolink India Pvt. Ltd. COMPANY PROFILE



For years, Carbolink India has been the Quality Leader in offering excellent Construction Chemical Products with Supreme Quality and Reliability.

Carbolink India Manufactures Industrial Flooring(Epoxy & PU Flooring), Decorative Flooring, 3D Flooring, Waterproofing Systems, corrosion protection, wood coatings, etc. which cater specifically to the Indian climate. With manufacturing facility in India, Carbolink India manufactures and supply Materials all through the country. Carbolink's commitment to customer service and technical support is the best. We work closely with architects, structural engineers, contractors and owners to best understand their requirements. Together we develop a best solution for a construction project, adding value and becoming more than just a materials supplier, but a solution provider.

With the support of our multinational manufacturing group, Carbolink India today has support centers across the country, strategically placed to provide consistent high standards of product and service.

Our Product Range:

- Anti Corrosive Coatings
- Car Park Flooring
- Curing Compounds
- Decorative Flooring
- Floor Hardner
- Grouts & Anchors



- Industrial Flooring
- Repairing Compunds
- Sealants
- Sports Flooring
- Tiling Products
- Wood Coatings



## Repairing Compounds

Repairing Compound is fast setting, hydraulic cement product formulated to stop leaks in concrete and masonry surfaces. It is particularly effective for stopping the flow of running water. Repairing Compounds are ready to use and requires only the addition of water before plugging and sealing cracks.

Carbolink manufactures a full range of world class Repairing Compounds systems providing the most up-to-date technologies. Carbolink India is a leader in tailored Repairing Compounds Solutions.

Here is our Technical Description of CLI Crack Seal (AC 100) :





# CLI Crack Seal ( AC 100 )

## Crack Sealer

### DESCRIPTION

CLI Crack Seal 100 is a crack sealer that cures to remains flexible to accommodate thermal or structural movement in small cracks.

### ADVANTAGES

- Flexible material that allows for small movement
- Remains flexible in all normal climates
- One part product allows a long pot life for ample installation period
- Waterproof

### APPLICATION

- Internal and External masonry wall cracks

### APPLICATION METHODOLOGY

- Surface must be clean and sound. All oil, dirt, debris, paint and any other material that might be a bond breaker must be removed. The final step in cleaning should be the complete removal of all residues with a vacuum cleaner or pressure washing.
- Widen the cracks wherever possible in V Groove shape.
- The crack must be pre-dampened for proper adhesion of the PlastiSeal.
- Requires no pre –mixing.
- Use the material directly from the container.
- Place CLI Crack Seal 100 directly into the damp crack with a spatula or putty knives and level with the surface. For deeper cracks, penetration and shrinkage are observed. In such cases repeat the application till the crack is leveled. For hairline cracks wherever widening is not possible, thin CLI Crack Seal 100 with potable and soft water to enable penetration.

### CHARACTERSTICS

Physical Appearance	WhiteThixotropic Paste
Full cure, days	7
Chemical Resistance – fully cured samples	
• Water	Excellent
• Gasoline	Excellent
• Oil	Excellent
• Salts (5% Calcium Chloride)	Excellent

### CLEANING & MAINTENANCE

Clean tools and equipment with water before the material hardens

### HEALTH & SAFETY

- Use goggles and hand gloves and mask during application.
- Clean hands with warm soap water after application.

### PACKING

Available in 1 kg pack

### STORAGE AND SHELF LIFE

Keep in a cool and dry place under shed away from heat. The shelf life of product is 9 Months in original unopened sealed condition.

### CONDITIONS OF SALE

Sold subject to the Company's conditions of sale which are available on request.

### NOTE

The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

**India's Most Trusted  
Construction Chemical Manufacturing Brand**



**Carbolink India Pvt. Ltd.**  
105, 1st Floor, Bhavya Sree Arcade,  
Above BATA, Erragadda,  
Hyderabad- 500018, INDIA  
Tel : +91 2370 0524, 2381 0264  
Email : [info@carbolinkindia.com](mailto:info@carbolinkindia.com)