



AC-Thinner

High-Quality Solvent used for Cleaning

Pack Size
5Kg & 1Kg

TDS
Technical Data Sheet



Product Description

AC Thinner is a versatile solvent designed for diluting single-pack enamels and primers. It enhances the flow of alkyd and oil-based products, ensuring optimal film characteristics. Additionally, it can be used for degreasing and cleaning heavily soiled bare metals.

Recommended Use

AC Thinner is ideal for use with alkyd-based enamel colors, clears, varnishes, and wood and metal primers as both a thinner and a cleaner.

Features & Benefits

- Improves paint consistency
- Allows paint to achieve optimal film characteristics
- Fast drying with a professional gloss finish
- Effective in removing wax and grease prior to spraying

Technical Data

Color	Clear Transparent
Odor	Mild aromatic
Specific Gravity	~0.79 ± 0.02
Flash Point	>35°C
Shelf Life	Best before 12 months in PET bottle

Application Notes

The ratio of thinner to paint should be in accordance with the paint manufacturer's guidelines. A general recommendation is to use 1 part thinner to 4 parts paint.

Health & Safety Instructions

]Flammable. Keep away from sources of ignition. Do not smoke. Work only in well-ventilated areas. When used indoors, always keep doors and windows fully open during application and drying. For short-term applications, a suitable cartridge mask may be worn, provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.

When applying paint, it is advisable to wear suitable eye protection. Keep the container tightly closed and out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses. Contains no added mercury.

Safety Precautions

In case of eye contact, flush eyes with warm water immediately and seek medical advice. For skin contact, wash thoroughly with soap and water or an approved industrial cleaner. Do not use solvents or thinners. If inhaled, move to fresh air, loosen clothing, and keep the patient rested. In case of ingestion, do not induce vomiting. Seek immediate medical attention.

Storage & Packing

Store in a cool, dry, and well-ventilated place, away from moisture, heat, and direct sunlight.

Pack Size

5Kg & 1Kg



Data Reliability

All technical data provided in this document are based on laboratory tests. Actual performance may vary due to factors beyond our control.

Regional Compliance

Product specifications may vary based on local regulations. Please refer to the local Product Data Sheet for precise information.

Legal Disclaimer

The information and recommendations regarding the application and end-use of Carbolink products are provided in good faith based on our current knowledge and experience. Due to variations in materials, substrates, and actual site conditions, no warranty of merchantability or fitness for a specific purpose can be inferred. The user must determine the product's suitability for the intended application. Carbolink reserves the right to change the properties of its products. All proprietary rights of third parties must be observed. Orders are subject to our current terms of sale and delivery. Always refer to the most recent local Product Data Sheet, available upon request.