



Luxury Wall Texture

Acrylic Wall Texture

Pack Size
25Kgs

TDS Technical Data Sheet



Product Description

Luxury Wall Texture is a premium, styrene-acrylic-based, white texture paint designed for both interior and exterior applications. This heavy-bodied, durable coating offers a rough finish that decorates and protects a wide range of surfaces by filling in pores and imperfections.

Product Advantages

- Provides a textured finish in white color.
- Effectively conceals surface imperfections and cracks.
- High resistance to fungus and algae growth.
- Exceptional durability and long-lasting performance.
- Easy to apply with excellent coverage.

Uses

Luxury Wall Texture is suitable for industrial, commercial, and residential structures. It can be applied to both new and previously painted surfaces including concrete, masonry, stucco, brick, drywall, fiber/cement boards, and properly prepared wood and metal surfaces.

Technical Data

Product Type:	Styrene Acrylic Resin
Finish:	Flat (1° - 3°) at 60° Geometry
Solids by Weight:	66 ± 2%
Solids by Volume:	46 ± 2%
Weight/Gallon:	12.71 ± 0.05 lbs. (5.77 ± 0.02 kg)
Color:	White
Drying Time:	To touch: 30 - 60 minutes To recoat: 2 - 4 hours

Coverage:	Theoretical: Up to 744 sq. ft. per gallon @ 1 mil Recommended: 80-100 sq. ft./gal. @ 9 dry mils, 20 wet mils
Sizes Available:	1 gallon, 5 gallons
• Thinning:	Not recommended
• Flash Point:	Non-flammable
• Viscosity:	130 - 135 KU
• Percent Pigment by Weight:	54 ± 2%
• VOC:	<120 g/L

Recommended Paint Systems

New & Previously Painted Concrete Walls:

- **Primer:** Apply one coat of Prime AC 31 B (400-450 sq. ft./gal. @ 1.4 dry mils, 4 wet mils)
- **Paint:** Apply one coat of Luxury Wall Texture (80-100 sq. ft./gal. @ 9 dry mils, 20 wet mils)

Porous Surface Walls:

- **Primer:** Apply one coat of Prime AC 31 B (400-450 sq. ft./gal. @ 1.4 dry mils, 4 wet mils)
- **Paint:** Apply one coat of Luxury Wall Texture (80-100 sq. ft./gal. @ 9 dry mils, 20 wet mils)

Surface Application Recommendations

- **Mildewed Surfaces:** This paint inhibits mildew growth on the dried paint film. Remove existing mildew by scrubbing with a solution of one part bleach to three parts water. Rinse thoroughly and let dry.
- **Concrete Surfaces:** Ensure mortar, plaster, stucco, and concrete block surfaces are cured and hardened. Remove any contaminants and ensure the pH level is below 9 before applying primer or paint.
- **Efflorescence:** Remove efflorescence using a solution of one part muriatic acid to three parts water. Rinse thoroughly.

Method of Application

Stir thoroughly before use. Apply with a brush, roller, or sprayer. Do not dilute the paint. Apply when the surface and air temperatures are above 50°F (10°C). Avoid applying in high humidity or when rain is expected. For best results, apply two full coats, allowing each coat to dry overnight.

Precaution

Avoid adding mineral spirits or solvents to the product. Apply generously but do not overspread. Stop painting at least two hours before dew formation or temperature drops below 50°F (10°C).

Health & Safety

Harmful if swallowed. Avoid contact with eyes and skin. Use adequate ventilation during application. Wear goggles and protective clothing as needed. In case of eye contact, flush with water. If swallowed, do not induce vomiting; seek medical attention immediately. Keep out of reach of children.

Packing & Storage

Store in a clean, dry area, protected from direct sunlight and extreme temperatures. Unopened containers can be stored for up to 12 months.

Pack Size

25Kgs



Data Reliability

All technical data provided in this document are based on laboratory tests. Actual performance may vary due to factors beyond our control.

Regional Compliance

Product specifications may vary based on local regulations. Please refer to the local Product Data Sheet for precise information.

Legal Disclaimer

The information and recommendations regarding the application and end-use of Carbolink products are provided in good faith based on our current knowledge and experience. Due to variations in materials, substrates, and actual site conditions, no warranty of merchantability or fitness for a specific purpose can be inferred. The user must determine the product's suitability for the intended application. Carbolink reserves the right to change the properties of its products. All proprietary rights of third parties must be observed. Orders are subject to our current terms of sale and delivery. Always refer to the most recent local Product Data Sheet, available upon request.