

Product Description

Prime AC 31 B is an acrylic polymerized, water-based primer designed to provide a sound base for wall coatings. It offers good alkali resistance properties, making it ideal for both interior and exterior applications.

Advantages

Easy to apply. Excellent hiding property.

Fast drying.

Excellent coverage.

Application

- Clean the surface thoroughly and remove all foreign material, including oil and grease.
- Remove laitance with a wire brush.
- Ensure all peeled-off or flaked paint is removed from previously painted surfaces.
- · Dust down the entire surface.
- Dilute Prime AC 31 B with fresh water at a ratio of 1:1.
- Apply a uniform coat of Prime AC 31 B with a brush, roller, or by spraying.
- Do not apply Prime AC 31 B when humidity is over 95% or when ambient temperature is not above 3°C of dew point.

Characteristics

Colour:	White.
Drying Time:	2 hours.
Specific Gravity @ 30°C:	1.35 - 1.39.
Theoretical Coverage:	8-10 m ² /L (1:1 dilution with water).
Flash Point:	Non-flammable.
Solid Content:	56-58%.
Viscosity:	16000 - 18000 cP.



Prime-AC-31B-TDS

DFT (Dry Film Thickness)

: 30 microns.

Pack Size

20Kg & 10Kg



Data Reliability

All technical data provided in this document are based on laboratory tests. Actual performance may vary due to factors beyond our control.

Regional Compliance

Product specifications may vary based on local regulations. Please refer to the local Product Data Sheet for precise information.

Legal Disclaimer

The information and recommendations regarding the application and end-use of Carbolink products are provided in good faith based on our current knowledge and experience. Due to variations in materials, substrates, and actual site conditions, no warranty of merchantability or fitness for a specific purpose can be inferred. The user must determine the product's suitability for the intended application. Carbolink reserves the right to change the properties of its products. All proprietary rights of third parties must be observed. Orders are subject to our current terms of sale and delivery. Always refer to the most recent local Product Data Sheet, available upon request.

