

Description

Carbolink's Pitch Mark is a water-based, concentrated, high-coverage coating specially formulated for marking grass playing fields.

Intended Uses

- Marking grass for soccer, rugby, cricket, hockey, netball, volleyball, and athletics tracks.
- · Painting logos on fields and other surfaces.
- · Creating temporary parking bays for special events.
- Demarcating areas for festivals and events.
- Marking trees for felling or directional arrows on tree bark.

Features

- Water-based, lead-free, solvent-free, VOC-free, and formaldehyde-free.
- Formulated to grow off with the grass, not wash off.
- Does not damage turf.
- Suitable for use with Automated Line Marking Machines.

Product Information

Appearance	Semi-Gloss.
Colour	Available in Black, Blue, Green, Orange, Red, White, and Yellow
Specific Gravity @ 25°C	1.33 depending on colour
Viscosity @ 25°C	75 to 80 seconds KU

Application Details

Mixing	Stir thoroughly with a flat paddle before adding to the tank.
Method	Spraying / Brush Application
Thinning	Water recommended.



Pitch Mark - TDS

Cleaning	Use water for cleaning.
Substrate	Suitable for grass, shale, clay, tarmac, and dirt surfaces.

Application Environment

Surface Temperature	Min 10°C or 2°C above dew point, Max 40°C
Ambient Temperature	Min 10°C or 2°C above dew point, Max 40°C
Relative Humidity	Min 10%, Max 85%

Drying time

Touch dry 30 min @ 25°C Dry to handle 60min @ 25°C Overcoating 4 hours@ 25°C

Storage

- Shelf life. 12 months from date of manufacture when correctly stored and unopened.
- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- · Keep containers tightly closed.

Transportation

Shipping Name: Not classified Packaging Group: Not classified

Hazard Class: 4-H-C

S.I.N/UN Number: Not classified as dangerous for transport

Surface Preparation

- Ensure turf is dry before applying Go-Mark
- · Stir Pitch Mark turf marking liquid thoroughly before use.
- Pour diluted Pitch Mark turf marking liquid through a strainer into line marking machine or application device.

Cautions

- Do not paint during inclement weather or if the temperature is below 10°C.
- Never add thinners/solvents to this product.
- Line marking machine or application device needs to be cleaned on a regular basis to remove sludge and contaminants. Failure to
 do so may result in product failure which is beyond the control of the manufacturer.

Safety Precautions

- · Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if symptoms persist.
- If ingested, give plenty of water or milk. Do not induce vomiting. Seek medical attention.
- Refer to the Material Safety Data Sheet for complete information.

Pack Size

20Kgs, 10Kgs & 5Kgs





Pitch Mark - TDS

Data Reliability

All technical data provided in this document are based on laboratory tests. Actual performance may vary due to factors beyond our control.

Regional Compliance

Product specifications may vary based on local regulations. Please refer to the local Product Data Sheet for precise information.

Legal Disclaimer

The information and recommendations regarding the application and end-use of Carbolink products are provided in good faith based on our current knowledge and experience. Due to variations in materials, substrates, and actual site conditions, no warranty of merchantability or fitness for a specific purpose can be inferred. The user must determine the product's suitability for the intended application. Carbolink reserves the right to change the properties of its products.

All proprietary rights of third parties must be observed. Orders are subject to our current terms of sale and delivery. Always refer to the most recent local Product Data Sheet, available upon request.

