



# Track kote - 40

Heavy Duty, High Built , 2  
Component Acrylic Based coating

Pack Size  
31.5Kgs & 15.75Kgs

TDS  
Technical Data Sheet



## Description

Carbolink Sports Track Kote 40 is a heavy-duty, high-build road surfacing material designed for durability and superior performance. This 2-component, cold-curing, solvent-free compound is based on acrylic resins and is ideal for screed applications.

## Features

- **Easy Application:** It can be easily applied with a texture roller.
- **High Durability:** Designed for long-lasting performance.
- **Excellent Adhesion:** Provides strong adhesion to both bitumen and concrete surfaces.
- **Specially Designed:** Ideal for accentuating bicycle tracks, footpaths, and area identification markings, as well as flat line markings

## Uses

- Cycle Track
- Jogging Track
- Running Track
- Skating Track.

## Technical Specifications

Viscosity	110±5 KU
Density	1.7±0.1 g/cm <sup>3</sup>
Skid Resistance	> 50 SRT.
Hardening Time:	Approximately 20 - 40 minutes, depending on ambient and surface temperature
Flashpoint	Approximately ten °C
Storage Stability:	6 months when stored in a cool place
Mixing Ratio	20:1
Pot Life (Mixed)	8-10 minutes at 20°C

## Application Method

Carbolink Sports Track Kote 40 is a heavy-duty, high-build road surfacing material designed for durability and superior performance. This 2-component, cold-curing, solvent-free compound is based on acrylic resins and is ideal for screed applications.

## Application Temperature

**Minimum:** > 10°C

**Maximum:** < 40°Ce.

## Health and Safety

Handle the product using appropriate safety measures to avoid skin and eye contact. Use in well-ventilated areas. Refer to the product's Safety Data Sheet (SDS) for detailed safety information.

## Packaging and Storage

Store in a cool, dry place away from direct sunlight and extreme temperatures. Keep the container tightly closed when not in use. Shelf life is six months.

## Pack Size

31.5Kgs & 15.75Kgs



## Data Reliability

All technical data provided in this document are based on laboratory tests. Actual performance may vary due to factors beyond our control.

## Regional Compliance

Product specifications may vary based on local regulations. Please refer to the local Product Data Sheet for precise information.

## Legal Disclaimer

The information and recommendations regarding the application and end-use of Carbolink products are provided in good faith based on our current knowledge and experience. Due to variations in materials, substrates, and actual site conditions, no warranty of merchantability or fitness for a specific purpose can be inferred. The user must determine the product's suitability for the intended application. Carbolink reserves the right to change the properties of its products. All proprietary rights of third parties must be observed. Orders are subject to our current terms of sale and delivery. Always refer to the most recent local Product Data Sheet, available upon request.